

PESTPRO 2000 BACKPACK SPRAYER USER'S MANUAL

Safety Precautions

- Do not fill with a flammable, acid, or caustic liquids.
- Do not adjust the tip or change spray patterns while depressing the valve trigger.
- Sprayer filled with liquid is heavy, use caution when bending, leaning, or walking; bend at the knees, not at the waist.
- Do not store or transport the unit while tank is pressurized.

Before Starting

- Inspect the hose, tank gasket, discharge valves, and nozzle for signs of wear or damage. These parts must be in full working condition to permit tank pressurization.
- Inspect the tank for unused pesticide; dispose of dilution according to label directions; clean tank before adding new insecticide.

Operating Instructions

Filling and Mixing

- Mix insecticides with the proper amount of water in a separate container.
- Note gallon marks on the side of the tank and fill accordingly.
- Add dilute insecticide to tank, then pump the sprayer handle to prime the pump and fill the pressure cylinder. The liquid in the tank will decrease as the cylinder is filled, add more liquid to fill the tank.
- Mix all insecticides according to label directions.

Pressurizing the Tank

- Pumping the sprayer handle several times will pressurize the tank.
- To relieve pressure open the cap.

Operation

The PestPro Backpack Sprayer is designed for a variety of professional uses, such as outdoor perimeter spraying for crawling insects and mosquitoes.

Application Rates: 4 Way Tip

50° coarse fan = 14.1 oz/min 80° fine fan = 6.4 oz/min Pin stream = 8.9 oz/min (large) 4.5 oz/min (small)

Care and Maintenance

 Flush tank, valve, and extension with clean water regularly.

• Do not use ammonia-based cleaners, these will damage the brass parts.

Clean the filter at the hose/valve connection regularly.

- Do not use metal objects to clean the orifices in the nozzle, this will disrupt the liquid spray pattern.
- Use the B&G Cleaning Kit (#22028000) for regular maintenance and cleaning of the sprayer.

Note: Residue from wettable powder (WP), soluble powder (SP), and some flowable (F) formulations can obstruct the pump cylinder and valve of the PestPro Sprayer. Regular flushing with clean water is required to keep the sprayer operating properly. Consider weekly cleaning when the sprayer is in daily use.



Problem: Tank not holding pressure **Solution:** • Tighten tank cap

Lubricate tank gasket when dry

Problem: Holds pressure, but will not spray

Solution: • Nozzle clogged, clean with a soft brush

• Clean strainer at the base of the valve, at the

hose / valve junction

Problem: Valve body leaking

Solution: • Replace 0-ring at base of handle; replace

copper gasket at base of valve stem (in

GT-100 Repair Kit

Problem: Tip Leaking

Solution: Clean or replace check valve at end of valve

extension

Problem: Handle locks up as if the tank is over-pressurized

Solution: • Remove hose from bottom of tank (at the pump

unit) to release air pocket



PESTPRO 2000 BACKPACK SPRAYER



REPLACEMENT PARTS

#	Order#	Description
1	33000309	Hose Assembly
2	22037500	XR Valve
3	22045600	Brass Extension
_	22032551	Check Valve / Strainer
_	22049451	5850 4-Way Tip
_	22032149	8004 Celcon Tip
_	22033101	Tip Cap Plastic
_	23083602	AV-210 Nozzle

B&G Help Line **800-544-8811**

